

# ZR108KCE-TF5

HFC, R-407C, 60Hz, 3- Phase, 200/230 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	106000	127000
Power (Watts):	9220	6550
Current (Amps):	28.00	21.80
EER (Btu/Wh):	11.50	19.40
Mass Flow (lbs/hr):	1540	1580
Sound Power (dBA):	80 Avg	85 Max
Vibration (mils(peak-peak)):	3.0 Avg	4.0 Max
Record Date:	2007-07-31	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	8.72
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	1059.85
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.00	Mounting Height (in):	21.75 *
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	110		
Net Weight (lbs):	132		
Internal Free Volume (in <sup>3</sup> ):	809.0		
Horse Power:	9		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	225.0	MCC (Amps):	47.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	27-Sep-1996
LRA Low*:		Max Operating Current:	35.5		
RLA(=MCC/1.4;use for contactor selection):	33.6				
RLA(=MCC/1.56;use for breaker & wire size selection):	30.1				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	50	3	200/220	Air Conditioning
R-134a HFC	60	3	200/230	Air Conditioning
R-407C HFC	50	3	200/220	Air Conditioning